

Category > Maintain

CFE 2000

High Performance Multi-Purpose Cleaner

Product Description

Ameripolish CFE 2000 is our latest cleaning solution designed to break down the toughest and most troublesome stains. CFE 2000 is very effective in environments where other aggressive chemicals are unsuccessful. CFE 2000 is eco-friendly and comes in a tilt-and-measure bottle for automatic scrubber use.

Features

- Cleans the toughest greases & oils
- Breaks down organic material
- Removes salts and minerals that can cause efflorescence
- Eco-Friendly
- Concentrate
- Usable in automatic scrubber

Uses

- Cleaning up grease and oil spills
- Applying to break down salts & minerals that would otherwise cause issues with efflorescence
- Removes tough organic stains

Dilution & Coverage

CFE 2000 can be diluted 8 parts water to 1 part CFE 2000 and sprayed directly onto problem areas.

CFE 2000 is also able to be used in an automatic scrubber at the proper mixing ratio.

8 ounce : 15 Gallons

16 ounce: 30 Gallons

Application

Apply CFE 2000 with a conical tip sprayer if treating a problem area. Spray a mist in circular motions on the problem area and then scrub with a brush vigorously to break down the targeted material.

(Automatic Scrubber)

Using the proper dilution ratio, pour 0.5oz for every 1 gallon of water to the automatic scrubber tank and use normally.

Product Specification

| | |
|---------------------|---------------------------------|
| Application: | Rag, Mop, or Automatic Scrubber |
| Appearance: | Clear/Milky |
| VOC: | Compliant (0g/L) |
| Shelf life: | Indefinite |

Packaging Specification

| Shipping Wt. | Unit |
|--------------|--------------------------------|
| N/A | Tilt and Measure 32oz Bottle |
| N/A | Other Quantities Made to Order |

Project Conditions: Ambient temperature during application should be 40-100°F. (4-38°C)

Remove all larger debris before using CFE 2000 with a sprayer or with and automatic scrubber.

Spills of staining agents or acidic etching agents including acidic food substances (e.g. vinegar, pickle juice) should be cleaned up immediately to minimize damage to surface.

Surface should be cleaned regularly using an automatic scrubber with Ameripolish® CFE 2000 mixed with water according to manufacturer's directions.

DO NOT use with acidic cleansers. Auto-scrubber should be fitted with non-aggressive cleaning tools such as brushes. Do not perform regular maintenance with aggressive pads such as diamond-impregnated pads or other abrasives. Use of aggressive pads will wear away stain protection and may, in time wear away color from concrete surface.

Cleanup

Rinse area with clean water to clean any area with excess dirt/product remaining on the floor.

Category > Maintain

CFE 2000

High Performance Multi-Purpose Cleaner

Storage

- Store upright in safe dry place at 40-105F° (4 -41C°)
- Keep product from freezing
- Keep out of reach of children
- Seal container after use
- Do not mix with other chemicals

VOC Compliance

In addition, Ameripolish® CFE 2000 offers VOC compliance with low VOC at 0g/L and is also compliant with national, state and district regulations:

- US Environmental Protection Agency
- California Air Resources Board SCM Districts*
- South Coast Air Quality Management District*
- Maricopa County, AZ
- Northeast Ozone Transport Commission*

*Before application, verify product conformance with local and state codes.

Warning & Safety Information

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. BEFORE USING THIS PRODUCT PLEASE READ THE SAFETY DATA SHEET IN ITS ENTIRETY! Safety Data Sheets (SDS) can be found online at www.ameripolish.com or upon request by contacting Ameripolish at 1-800-592-9320.

Warranty

The information contained herein is believed to be reliable. This information is based on laboratory testing and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer. Sole remedy shall be replacement of product proven defective.