

Category > Protect

PSE Paver Sealer Enhancer

Water-Based high performance polymer



Product Description

Ameripolish® PSE Paver Sealer Enhancer is a water-based high performance polymer that forms a breathable barrier that protects cementitious materials from salts, stains, dirt, oils and moisture. It has been formulated to rejuvenate and enhance the original color of pavers and concrete while providing long lasting weather protection against water penetration and UV degradation. Ideal for sealing interlocking pavers, colored cementitious material, stone, and other cement textured surfaces.

Features

- Breathable barrier prevents staining and seals out moisture
- Protects color from UV degradation
- Non-yellowing finish will not peel, crack, blister, or blush
- Environmentally safe
- Long lasting
- Prevents staining and reduces maintenance
- Can be shipped as non-hazardous material
- Easy application with a sprayer
- Low VOC (5 g/L)

Uses

Ameripolish® PSE Paver Sealer Enhancer is ideal to be used for sealing:

- Interlocking pavers
- Colored cementitious materials
- Stone
- Other cement textured surfaces

Dilution & Coverage

Ameripolish® PSE Paver Sealer Enhancer is a Ready to Use (RTU) product and should not be mixed with any other chemical. Approximate coverage rate is 400 - 600 sqft per gallon on standard surfaces and 300 - 400 sqft per gallon on very porous surfaces.

Product Specification

Application:	Spray on (2) coats (opposite directions)
Appearance:	Milky
VOC:	Compliant (5 g/l)
Shelf life:	3 years
Solvent:	Water-Based

Packaging Specification

Product #	Shipping Wt.	Container
PAVER-1	10 lbs.	1 gallons RTU
PAVER-5	50 lbs.	5 gallons RTU
PAVER-30	300 lbs.	30 gallons RTU
PAVER-55	550 lbs.	55 gallons RTU
PAVER-250	2,500 lbs.	250 gallons RTU



Category > Protect

PSE Paver Sealer Enhancer

Water-Based high performance polymer

Application

1. Spray in a circular motion using an Ameripolish® Pump Sprayer. Spray enough for complete coverage.
2. Do not puddle or leave drip marks. Spread with Ameripolish® Microfiber Pad evenly if necessary.
3. Apply additional applications to achieve a higher sheen.

Cleanup

Rinse all equipment and applicators with water shortly after using Ameripolish® PSE Paver Sealer Enhancer

Storage

- Store upright in safe dry place at 40-100F° (4 -38C°)
- Keep product from freezing
- Keep out of reach of children
- Seal container after use
- Do not mix with other chemicals

VOC Compliance

In addition, Ameripolish® PSE Paver Sealer Enhancer offers VOC compliance with low VOC at 5 g/L and is also compliant with several national, state, and district regulations:

- US Environmental Protection Agency
- California Air Resources Board SCD Districts*
- South Coast Air Quality Management District*
- Maricopa County, AZ
- Northeast Ozone Transport Commission

*Before application, verify product conformance with local and state codes.

Warning & Safety Information

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. BEFORE USING THIS PRODUCT PLEASE READ THE SAFETY DATA SHEET IN ITS ENTIRETY! Safety Data Sheets (SDS) can be found online at www.ameripolish.com or upon request by contacting Ameripolish at 1-800-592-9320.

Warranty

The information contained herein is believed to be reliable. This information is based on laboratory testing

and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer. Sole remedy shall be replacement of product proven defective.