

Category > Protect

G3

Burnishing Pad for 3D SP E

Product Description

Ameripolish® G3 is a floor burnishing pad for use on ultra high speed floor machines that operate in the 1500-3000 RPM range. The pad is made of polyester fibers in a non-woven construction. This product is designed for the burnishing phase after Ameripolish® 3D SP E is applied and dried. The pad is available in varying sizes.

Features & Uses

- Designed to improve gloss/clarity of floors protected with Ameripolish® 3D SP E or “guard” type products
- Removes dust, scuffs and marks on high traffic areas
- Used on ultra high speed electric, battery, or propane floor machines

Application

1. After the proper application of Ameripolish® 3D SP E as according to its TDS, secure the Ameripolish® G3 burnishing pad to a high speed burnisher.
2. Once the Ameripolish® G3 burnishing pad has been secured, operate the machine normally between 1500-3000 RPM.
3. It is not necessary to heat the 3D SP E sealer to a certain temperature, simply pass over the entire floor with the Ameripolish® G3 burnishing pad at a walking pace.

Sealed surface should be inspected periodically for areas of thin or traffic-worn sealer, and sealer reapplied as needed. Normal traffic may require reapplication of Ameripolish® sealers annually. Use Ameripolish® Rejuvenating Cleaner for long lasting protection during maintenance.

Cleanup

Remove dust and debris with broom, vacuum, water hose, mop or auto-scrubber.

Warranty

The information contained herein is believed to be reliable. This information is based on laboratory testing and results.

Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer. Sole remedy shall be replacement of product proven defective.

Product Specification

Application:	Burnishing
Appearance:	Lofty non-woven pad
Shelf life:	Indefinite

Packaging Specification

Product #	Shipping Wt.	Container
G3-21-2	4 lbs.	2 Pack
G3-24-2	5 lbs.	2 Pack
G3-27-2	7 lbs.	2 Pack

