

Category > Prepare

# Oil Ingester

## Water-Based Microbial Stain Remover



### Product Description

Ameripolish® Oil Ingester is a water-based microbial stain remover that consumes and breaks down oil-based stains and absorbs odors from the surface of concrete without causing damage or affecting any existing colorant, sealer, or stain protector. This biodegradable and VOC-compliant product is environmentally safe and can be used daily. Deeply embedded oil spots may take weeks to be removed; this is normal as oil tends to penetrate deep in the concrete. Oil Ingester eats away at the oil and does not wash it into WWTP or city drainage runoffs.

### Features

- Safely removes or lightens oil stains from most surfaces
- Stops oil from continually wicking to the surface
- Does not damage colorants, sealers or stain protectors
- Will not etch polished concrete
- Environmentally safe consumption
- Consumes & breaks down oil vs. only emulsifying
- No harsh acids or bases or solvents that can cause burning
- Reduces or removes odors
- Can be shipped as a non-hazardous material
- 100% biodegradable
- VOC-compliant

### Uses

- Ameripolish® Oil Ingester can be used on multiple surfaces such as cementitious materials, and most common substrates. It is designed to consume and breakdown oil and oil-based materials.
- Oil Ingester continually works on breaking down oil-based materials until it is washed away. It can continuously work for days/weeks on stains, breaking down the oils and consuming them.
- This product works most efficiently at temperatures above 55F°. Colder temperatures do not destroy the ability to breakdown oils but will significantly slow down the process.

### Product Specification

<b>Application:</b>	Dilute and spray as directed
<b>Appearance:</b>	Clear
<b>VOC:</b>	Compliant (0g/l)
<b>Shelf life:</b>	3 years
<b>Solvent:</b>	Water-Based

### Packaging Specification

Product #	Shipping Wt.	Container
OE5	10 lbs.	1 gallons (5 gallons RTU)
OE35	25 lbs.	5 gallons (25 gallons RTU)



Category > Prepare

# Oil Ingester

## Water-Based Microbial Stain Remover

### Dilution & Coverage

Ameripolish® Oil Ingester should be diluted with water:  
1:4 for oil removal (1 part water: 4 part product)  
9:1 for maintenance (9 parts water: 1 part product)

The coverage rate varies considerably from floor to floor.  
1 gallon of diluted product will cover approximately 200-400 sqft.

### Application

1. Clean concrete using a pressure washer to quickly remove surface grease, dirt and debris away from work area.
2. Spray the first application of Ameripolish® Oil Ingester over work area and let soak into concrete. Let first application dwell for a minimum of 1 week. Oil Ingester works better when wet; if possible maintain the problem area with a sprayed application on the days after the 1st application.
3. Thoroughly rinse working area and apply a second application of Ameripolish® Oil Ingester over work area. Let second application dwell for a minimum of 1 week. Oil Ingester works better when wet, if possible maintain the problem area with a sprayed application on the days after the 2nd application.
4. Repeat process (if needed) until oil stain has been removed.
5. For best results it is recommended to apply a minimum of 2-3 times.

### Cleanup

Oil Ingester cleans up easily with soap and water. Spray with soapy water to remove material from stain area. Ameripolish® Oil Ingester continues to work for long periods of time but will wash away with rain.

### Storage

- Store upright in safe dry place at 40-105F° (4 -41C°)
- Keep product from freezing
- Keep out of reach of children
- Seal container after use
- Do not mix with other chemicals

### VOC Compliance

In addition, Ameripolish® Oil Ingester offers VOC compliance with low VOC at 0 g/L and is also compliant with national, state, and district regulations:

- US Environmental Protection Agency
- California Air Resources Board SCM Districts\*
- South Coast Air Quality Management District\*
- Maricopa County, AZ
- Northeast Ozone Transport Commission

\*Before application, verify product conformance with local and state codes.

### Warning & Safety Information

**KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. BEFORE USING THIS PRODUCT PLEASE READ THE SAFETY DATA SHEET IN ITS ENTIRETY! Safety Data Sheets (SDS) can be found online at [www.ameripolish.com](http://www.ameripolish.com) or upon request by contacting Ameripolish at 1-800-592-9320.**

### Warranty

The information contained herein is believed to be reliable. This information is based on laboratory testing and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer. Sole remedy shall be replacement of product proven defective.