

Category &gt; Prepare

# Strip & Clean

## Water-Based Stripping Agent



### Product Description

Ameripolish® Strip & Clean is a water-based stripping agent specifically formulated for the grind-free removal of the Ameripolish® 3D SP sealer from polished concrete floors. Strip & Clean also is a great tool to prepare exterior concrete for ColorJuice applications. It helps remove mold, mildew and other contaminants that would otherwise impair the project

### Features

- Grind-free sealer removal
- Formulated specifically for removal of Ameripolish “guard” type sealers
- Biodegradable, low odor and non-flammable
- Safely remove improperly installed “guard” type sealers
- Ideal for preparation for dye reapplication

### Uses

Ameripolish® Strip & Clean is a water-based stripping agent specially formulated for the removal of the Ameripolish® Sealers from polished concrete floors that have received the Ameripolish® dyes.

- Reapply dye to an existing project
- Reinstall improperly installed “guard” type products.
- Cleans up mold & mildew on the surface of concrete
- Prepare oil spots for Ameripolish® Oil Ingester applications

### Dilution & Coverage

Ameripolish® Strip & Clean is shipped ready to use (RTU) and can be diluted with water.

- Proper Dilution Ratio is 1:1 with water

### Application

Strip & Clean comes as a concentrate that can be used at full strength for maximum effect or can be diluted to extend coverage rates

### Product Specification

<b>Application:</b>	Spray and brush
<b>Appearance:</b>	Orange/Clear Liquid
<b>VOC:</b>	Compliant (0g/L)
<b>Shelf life:</b>	3 years
<b>Solvent:</b>	Water-based

### Packaging Specification

Product #	Shipping Wt.	Container
SS2	9 lbs	1 gallon
SS5	44.5 lbs	5 gallons
SS30	268 lbs	30 gallons
SS55	488.5 lbs	55 gallons



Category > Prepare

# Strip & Clean

## Water-Based Stripping Agent

1. Apply Strip & Clean to surfaces by conical tip sprayer. Make sure the surface is fully covered and allow Strip & Clean to work a minimum of 10 minutes.
2. After 10 minutes, scrub the surface using a brush or scrubbing machine.
3. After scrubbing, rinse the surface thoroughly with water and vacuum up to remove any surface material.
4. Make sure the remaining excess material is cleaned up before proceeding to apply other chemicals and colorants.

### Cleanup

Rinse all equipment and applicators with water shortly after using Strip & Clean.

### Storage

- Store upright in safe dry place at 40-100°F (4-38°C)
- Keep product from freezing
- Keep out of reach of children
- Seal container after use
- Do not mix with other chemicals

### VOC Compliance

In addition, Ameripolish® Strip & Clean offers VOC compliance with low VOC at 0g/L and is also compliant with national, state, and district regulations:

- US Environmental Protection Agency
- California Air Resources Board SCM Districts\*
- South Coast Air Quality Management District
- Maricopa County, AZ
- Northeast Ozone Transport Commission

\*Before application, verify product conformance with local and state codes.

### Warning & Safety Information

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. BEFORE USING THIS PRODUCT PLEASE

READ THE SAFETY DATA SHEET IN ITS ENTIRETY! Safety Data Sheets (SDS) can be found online at [www.ameripolish.com](http://www.ameripolish.com) or upon request by contacting Ameripolish at 1-800-592-9320.

### Warranty

The information contained herein is believed to be reliable. This information is based on laboratory testing and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer. Sole remedy shall be replacement of product proven defective.